

DECLARATION OF PERFORMANCE



DOP NC5.2-0.55ALLSPC

1.	Unique identification code of the product-type:			
	SPC flooring RC55 5.2mm / 0.55 mm wear layer			
2	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specifi- cation, as foreseen by the manufacturer:			
	For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.			
3	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):			
	HMTX Global, Argon 37, 4751XC Oud Gastel, Netherlands			
1	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):			
7	where applicable, hand contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2).			
5	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:			
	System 3			
6	In case of the declaration of performance concerning a construction product covered by a harmonised standard:			
	Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).			
	Ghent University - Centre for Textile Science and Engineering is authorized as a notified body 0766		not applicable	
	certificate No FLO-24-06-17-02			
	Notified Body		certificate of constancy of performance	
7	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:			
	not applicable			
8	Declared performance			
	Essential characteristics	Performance	Harmonised technical specification	
	Reaction to fire	Bfl s1	EN 14041:2004+AC:2005+AC:2006	
	Content of Pentachlorophenol	NPD	EN 14041:2004+AC:2005+AC:2006	
	Formaldehyd Emissions	Class E1	EN 14041:2004+AC:2005+AC:2006	
	Slip resistance	DS	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (dissipative)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (conductive)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Electrical behavior (antistatic)	NPD	EN 14041:2004+AC:2005+AC:2006	
	Thermal conductivity [W/mK]	NPD	EN 14041:2004+AC:2005+AC:2006	
	Water-tightness	NPD	EN 14041:2004+AC:2005+AC:2006	
9.	The performance of the product identified in points 1 is in contributed in points 2 is in contributed in points 3 is in contri			
	Graca Rocha , Sustainability & Quality Manager			
	(name and function)		Graca Rocha	
	Netherlands, March 2024			
	(place and date of issue)		(signature)	