

tesa® 4024

Universal carton sealing tape

tesa® 4024 PV 2 is based on a PP backing coated with a special high tack water based acrylic adhesive. The excellent tack of the adhesive secures a good sealing immediately after application.

tesa® 4024 PV 2 has the following additional features:

- Low noise unwinding.
- Excellent ageing resistance.
- It can be used on all common hand dispensers and machines.

As the product is chlorine free and based on derivatives of mineral oil only, the disposal by heat treatment is environmental friendly.

The process of cardboard waste recycling will be not disrupted as confirmed by leading recycling companies and paper mills.

Main Application

Manual and automatic sealing of light and medium-range weight cartons.

Technical Data

| | | | |
|--------------------|---------|-----------------------|---------|
| ▪ Backing material | PP film | ▪ Adhesion to steel | 3 N/cm |
| ▪ Total thickness | 52 µm | ▪ Elongation at break | 140 % |
| ▪ Type of adhesive | acrylic | ▪ Tensile strength | 45 N/cm |

Properties

| | | | |
|-------------------------|-----|-----------------------|-------|
| ▪ Automatic application | yes | ▪ Printability | ● ● ● |
| ▪ Manual application | yes | ▪ Low noise unwinding | yes |

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

The PV3-version of the product is printable.

For latest information on this product please visit <http://l.tesa.com/?ip=04024>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.