

## tesa® 4101 PV2

### Adhesive film of hydrate cellulose for packaging

tesa® 4101 PV 2 is based on a hydrate cellulose film coated with a rubber adhesive. The backing, which is composed of a sustainable material, is characterized by a high rigidity and low electrostatic charging. For this reason long strips of the tape can be dispensed without any curling effect is possible. The tape can easily be torn by hand.

Hydrate cellulose film can be cleanly cut (separated) by an subjacent tesa® tear strip.

### Main Application

tesa® 4101 PV 2 is mainly used for general packaging purposes, such as sealing of small boxes. The tape can be easily applied with tesa® desk dispensers.

### Technical Data

▪ Backing material	hydrate cellulose	▪ Adhesion to steel	6 N/cm
▪ Total thickness	51 µm	▪ Elongation at break	25 %
▪ Type of adhesive	synthetic rubber	▪ Tensile strength	42 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=04101>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.