

tesa® 4204 PV6

Transparent packaging tape

The properties of the adhesive enable a good tack on all kind of surfaces and secure a good sealing.

The ageing stability allows long storage times.

Compared to most other PP waterbased acrylic tapes tesa® 4204 PV 6 has an improved adhesive anchorage, which reduces the risk of adhesive residues after removal.

The label protection application can be easily achieved with all common label protection dispensers.

As the product is chlorine free and based on derivatives of mineral oil only, the disposal by heat treatment is environmental friendly.

The process of cardboard waste recycling will be not disrupted as confirmed by leading recycling companies and paper mills.

Main Application

tesa® 4204 PV 6 is recommended for automatic sealing of bags, tins, drums and for high quality label protection.

Technical Data

▪ Backing material	PP film	▪ Adhesion to steel	2.8 N/cm
▪ Total thickness	58 µm	▪ Elongation at break	150 %
▪ Type of adhesive	acrylic	▪ Tensile strength	50 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=04204>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.