

## tesa® 4206

### Highly transparent adhesive film

tesa® 4206 is based on a highly transparent PP-film backing and is coated with an extremely non-aging and light-resisting adhesive.

tesa® 4206 is characterised by smooth and low noise unwinding features.

### Main Application

tesa® 4206 is universally used for:

- packaging applications where high transparency and very good aging stability are needed
- mounting of litho films
- label protection on chemical bottles
- splicing of film (photo-printing)

### Technical Data

▪ Backing material	PP film	▪ Adhesion to steel	3.4 N/cm
▪ Total thickness	58 µm	▪ Elongation at break	150 %
▪ Type of adhesive	acrylic	▪ Tensile strength	43 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=04206>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.