

tesa® 4319

Flexible masking tape for paint work - especially for curves

With the tesa® flexible masking tape you will ace every curve. The quality of the crepe allows this flexible masking tape to be adapted perfectly to any curvature. Thanks to the thick adhesive padding, this flexible masking tape holds reliably even on rough surfaces, thus avoiding ugly paint tears. The curves specialist from tesa® makes perfect painting work possible even under difficult conditions. With the combination of high-quality surface protection tape and sound workmanship you will achieve optimum working results. The flexible masking tape saves you corrections that are time-consuming.

Main Application

- Especially suitable for masking of curves
- Rapid, reliable masking off, even on rough surfaces
- Indoor masking

Technical Data

▪ Backing material	highly-creped paper	▪ Adhesion to steel	4.5 N/cm
▪ Total thickness	375 µm	▪ Elongation at break	58 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	28 N/cm

Properties

- | | | | |
|-------------------------------|------|-------------------|------|
| ▪ Hand tearability | ●●●● | ▪ Paint anchorage | ●●●● |
| ▪ Suitable for rough surfaces | ●●●● | | |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Recommendation:

Stretching the crêped backing guarantees evenly defined paint edges and a good adhesion.

For latest information on this product please visit <http://l.tesa.com/?ip=04319>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.