

## tesa® 4325

### General purpose masking tape

tesa® 4325 is a finely creped paper masking tape with a natural rubber adhesive

### Main Application

- Indoor applications
- General purpose applications
- Masking during paintwork
- Fixing masking materials
- Sealing, packaging, bundling

### Technical Data

▪ Backing material	slightly-creped paper	▪ Adhesion to steel	2.6 N/cm
▪ Total thickness	120 µm	▪ Elongation at break	10 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	33 N/cm

### Properties

- |                    |      |                     |     |
|--------------------|------|---------------------|-----|
| ▪ Hand tearability | ●●●● | ▪ Sharp colour edge | ●●● |
| ▪ Paint anchorage  | ●●●● |                     |     |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04325>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.