

tesa® 4443

Special masking tape with PP-Liner for a good plottability

tesa® 4443 is a special masking tape with a tough, resistant, stabilized paper backing and a strong adhesive. It is available with a special PP-Liner for easy processing on computer controlled systems like flatbed and roll plotters without sprocket feed.

Stencil Material for Sandblasting with a Maximum Durability of 6 sec/4 bar for use on Plotter Systems.

Main Application

Due to the smooth and resistant backing of the stencil material, tesa® 4443 is suitable for surface sandblasting on glass and stone.

Technical Data

▪ Backing material	flat paper	▪ Elongation at break	6 %
▪ Total thickness	330 µm	▪ Tensile strength	93 N/cm
▪ Type of adhesive	acrylic	▪ Temperature resistance	100 °C
▪ Adhesion to steel	4.5 N/cm		

Properties

▪ Plottability	● ● ● ●	▪ Sharp colour edge	● ● ●
▪ Suitable for sandblasting	● ● ●	▪ Conformability	● ●
▪ Paint anchorage	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04443>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.