

## tesa® 4541

### Conformable uncoated cloth tape

tesa® 4541 is a highly tear-resistant uncoated cloth tape. It is based on a 145 mesh rayon fabric backing and natural rubber adhesive.

tesa® 4541 is a very flexible and conformable tape convenient for a wide range of applications.

#### Features:

- good adhesion even on rough and oily surfaces
- adapts to uneven surfaces without creasing
- easy to write on, ideal marking tape
- very high tensile strength
- smooth and conformable
- available in 5 colours: black, white, grey, red, brown

### Main Application

- Manual and machine driven closure of heavy cartons, buckets and tins
- Sealing of film containers, junction boxes and gap closures
- Bundling of bars, rods and cables
- Cable harnessing
- Securing of edges
- Reinforcing of book covers
- Fixing of plastic clips to cable tubes
- Reinforcing of hockey sticks
- Various applications in animal health care for bandaging large and small animals

### Technical Data

▪ Backing material	uncoated cloth	▪ Tensile strength	90 N/cm
▪ Total thickness	270 µm	▪ Temperature resistance (30 min)	130 °C
▪ Type of adhesive	natural rubber	▪ Mesh	145 count per square inch
▪ Adhesion to steel	3.6 N/cm	▪ Surface finish	matt
▪ Elongation at break	16 %		

### Properties

- |                    |     |                       |     |
|--------------------|-----|-----------------------|-----|
| ▪ Easy to write on | yes | ▪ Abrasion resistance | ●●● |
|--------------------|-----|-----------------------|-----|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

### Additional Information

Complies with LV 312-1 Dielectric strength.

For latest information on this product please visit <http://l.tesa.com/?ip=04541>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.