

tesa® 4657

Temperature resistant acrylic coated cloth tape

tesa® 4657 is a high grade acrylic coated cloth tape. It is based on a 145 mesh woven cotton fabric and a thermosetting natural rubber adhesive.

tesa® 4657 is a very resilient cloth tape often used for permanent hole covering in automotive applications and masking during industrial painting processes.

Features:

- removable without residues even after high temperature exposure
- very ageing-resistant (allowing for permanent applications)
- high resistance to paint solvents
- excellent tape for die-cuts, available as log roll with liner as tesa® 4657 PV9
- also available as low unwinding version tesa® 4657 PV 1
- available in 2 colors: black, grey

Main Application

- Heat resistant masking during the production of vehicles and machines
- Window flange masking
- Even repeated oven drying possible
- Permanent interior and exterior hole covering
- Covering of screw tap holes and drainage boreholes
- Partial masking during treatment with impregnating agents
- Fastening of flat cables e.g. on roof linings, door panels, mirrors
- Masking during electrostatic powder coating

Technical Data

▪ Backing material	acrylic-coated cloth	▪ Elongation at break	7.5 %
▪ Total thickness	290 µm	▪ Tensile strength	105 N/cm
▪ Type of adhesive	thermosetting natural rubber	▪ Temperature resistance (30 min)	180 °C
▪ Adhesion to steel	4.6 N/cm	▪ Mesh	145 count per square inch

Properties

▪ Hand tearability	● ● ● ●	▪ Suitable for die cutting	yes
▪ Straight tear edges	● ● ● ●	▪ Certified according to	all major OEMs
▪ Easy to remove	yes	▪ Abrasion resistance	● ● ● ●
▪ Easy to write on	yes	▪ Water resistance	● ● ●

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04657>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® 4657

Temperature resistant acrylic coated cloth tape

Additional Information

Complies with LV 312-1 Dielectric strength.

For latest information on this product please visit <http://l.tesa.com/?ip=04657>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.