

tesa® 4836

Double sided masking tape for designing masks in all formats

With the tesa® double sided masking tape 4836 you can design masks in all formats. This double sided masking tape is easy to use and holds protective masking material firmly in place. Adhesive on both sides of the masking tape allows you to make individual protective masks and to use it for large areas outdoors in particular. Apply the open side first to the area you wish to cover, then apply the plastic masking foil on the reverse side to achieve large area masking protection during cleaning and renovation work like painting and plastering work. As there is a non-adhesive area on this side where the plastic masking foil shall be fixed, it is easy to grab the foil after work's done to detach it.

Main Application

- Indoor and outdoor applications
- Production of individual, large area masking

Technical Data

▪ Backing material	PVC film	▪ Adhesion to steel	3 N/cm
▪ Total thickness	130 µm	▪ Tensile strength	30 N/cm
▪ Type of adhesive	acrylic	▪ UV-resistance	6 weeks

Properties

- | | | | |
|--------------------|-------|------------------|-------|
| ▪ Hand tearability | ● ● ● | ▪ Conformability | ● ● ● |
|--------------------|-------|------------------|-------|

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04836>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.