

tesa® 4917

Double-sided filmic tape with differential adhesive system

tesa® 4917 consists of a transparent double-sided PP-film with a differential adhesive system. The product can easily be cut with the hot wire systems of common bag machine producers.

Main Application

- Reopenable closure system for filmic bags
- Removable emblems or profiles

Technical Data

▪ Backing material	PP film	▪ Type of liner	PP
▪ Color	transparent	▪ Colour of liner	red
▪ Total thickness	90 µm	▪ Thickness of liner	80 µm
▪ Type of adhesive	tackified acrylic		

Adhesion to

▪ Steel (initial)	8.2 N/cm	▪ Steel (after 14 days)	11.4 N/cm
▪ Steel (covered side, initial)	4.5 N/cm	▪ Steel (covered side, after 14 days)	4.1 N/cm
▪ ABS (initial)	6.9 N/cm	▪ ABS (after 14 days)	10.1 N/cm
▪ ABS (covered side, initial)	4.2 N/cm	▪ ABS (covered side, after 14 days)	6.0 N/cm
▪ Aluminium (initial)	7.7 N/cm	▪ Aluminium (after 14 days)	10.2 N/cm
▪ Aluminium (covered side, initial)	3.5 N/cm	▪ Alu (covered side, after 14 days)	4.7 N/cm
▪ PC (initial)	9.0 N/cm	▪ PC (after 14 days)	11.0 N/cm
▪ PC (covered side, initial)	4.0 N/cm	▪ PC (covered side, after 14 days)	6.8 N/cm
▪ PE (initial)	3.9 N/cm	▪ PE (after 14 days)	4.1 N/cm
▪ PE (covered side, initial)	1.6 N/cm	▪ PE (covered side, after 14 days)	2.3 N/cm
▪ PET (initial)	6.6 N/cm	▪ PET (after 14 days)	9.3 N/cm
▪ PET (covered side, initial)	3.1 N/cm	▪ PET (covered side, after 14 days)	4.7 N/cm
▪ PP (initial)	6.4 N/cm	▪ PP (after 14 days)	6.9 N/cm
▪ PP (covered side, initial)	2.7 N/cm	▪ PP (covered side, after 14 days)	2.6 N/cm
▪ PS (initial)	7.9 N/cm	▪ PS (after 14 days)	10.0 N/cm
▪ PS (covered side, initial)	3.8 N/cm	▪ PS (covered side, after 14 days)	5.6 N/cm
▪ PVC (initial)	6.5 N/cm	▪ PVC (after 14 days)	11.0 N/cm
▪ PVC (covered side, initial)	4.0 N/cm	▪ PVC (covered side, after 14 days)	7.0 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=04917>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® 4917

Double-sided filmic tape with differential adhesive system

Properties

▪ Temperature resistance short term	120 °C	▪ Resistance to chemicals	● ● ●
▪ Temperature resistance long term	80 °C	▪ Softener resistance	● ●
▪ Tack	● ● ●	▪ Static shear resistance at 23°C	● ● ●
▪ Ageing resistance (UV)	● ● ● ●	▪ Static shear resistance at 40°C	● ● ●
▪ Humidity resistance	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

tesa® 4917 is also available with fingerlift (extended liner) for fast liner removal.

For latest information on this product please visit <http://l.tesa.com/?ip=04917>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.