

tesa® 4964

Double-sided tape with fabric backing

tesa® 4964 consists of a tear resistant flexible fabric backing with a rubber adhesive system.

The adhesive has a high coating weight making it well suited for mounting applications on irregular surfaces.

tesa® 4964 can be removed in most cases without leaving adhesive residues from sound surfaces.

Initial tests should be carried out before mounting tesa® 4964 on plasticised surfaces

Main Application

- Carpet laying
- Honeycomb milling
- Laminating of shoe insoles and heel protectors (leather manufacturing)
- Splicing of fabric webs

Technical Data

▪ Backing material	cloth	▪ Type of adhesive	natural rubber
▪ Color	white	▪ Elongation at break	10 %
▪ Total thickness	390 µm	▪ Tensile strength	80 N/cm

Adhesion to

▪ Steel (initial)	7.5 N/cm	▪ Steel (after 14 days)	7.6 N/cm
▪ ABS (initial)	7.3 N/cm	▪ ABS (after 14 days)	7.8 N/cm
▪ Aluminium (initial)	7.2 N/cm	▪ Aluminium (after 14 days)	7.3 N/cm
▪ PC (initial)	7.4 N/cm	▪ PC (after 14 days)	7.5 N/cm
▪ PE (initial)	5.3 N/cm	▪ PE (after 14 days)	5.4 N/cm
▪ PET (initial)	6.5 N/cm	▪ PET (after 14 days)	7.2 N/cm
▪ PP (initial)	6.8 N/cm	▪ PP (after 14 days)	6.9 N/cm
▪ PS (initial)	7.2 N/cm	▪ PS (after 14 days)	7.5 N/cm
▪ PVC (initial)	6.9 N/cm	▪ PVC (after 14 days)	7.0 N/cm

Properties

▪ Tack	●●●●	▪ Softener resistance	●●●
▪ Ageing resistance (UV)	●●	▪ Static shear resistance at 23°C	●●
▪ Humidity resistance	●●	▪ Static shear resistance at 40°C	●
▪ Resistance to chemicals	●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04964>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® 4964

Double-sided tape with fabric backing

Additional Information

Additional product versions specially designed for the honeycomb milling application:

PV15: Double sided tape with fabric backing; brown glassine paper liner

Liner variants:

PV0: Brown glassine paper (standard)

For latest information on this product please visit <http://l.tesa.com/?ip=04964>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.