

## tesa® 6056

### Semi-automatic bench dispenser

tesa® 6056 is a bench dispenser with pre-set length control and electromagnetic cross-cutter. It is universally applicable for nearly all kinds of tesa® self-adhesive tapes up to 50 mm width, particularly cloth and paper tapes. Even difficult to cut materials are cut perfectly. Due to the electromagnetic triggered transverse blade a smooth clean cut is achieved.

### Main Application

The desired strip length is set on the measuring scale on the left-hand side of the dispenser in a range from 30 to 150 mm. The tesa® tape is unrolled by hand until the measuring roller prevents further tape to be dispensed. By pulling the tape gently downwards, the electromagnetic cross cutter is triggered via a microswitch. The desired strip is automatically cut for use. A single movement of the hand is, therefore, sufficient for unrolling, cutting and removing a tesa® strip of predetermined length. For strip longer than 150 mm, the measuring roller is switched to continuous operation. The tesa® automatic dispenser 6056 is equipped with a control unit to adjust the impact force of the electromagnetic cutter. Set a lower impact force for tapes which are easy to cut, such as filmic tapes of smaller widths, to minimize impact noise and dispenser strain.

### Technical Data

▪ Core diameter	3 inch	▪ Weight	5500 g
▪ Type of tape	single-sided	▪ Max. roll diameter	180 mm
▪ Application purpose	multifunctional	▪ Type of applicator	table
▪ Length	340 mm	▪ Max. roll width	50 mm
▪ Width	150 mm	▪ Length presetting up to	30-150 mm
▪ Height	133 mm	▪ Connections	230 V / 50 Hz
▪ Mode of drive	automatic	▪ Power supply	10 watt

For latest information on this product please visit <http://l.tesa.com/?ip=06056>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.