

tesa® Professional 4319

Flexible masking tape for paint work - especially for curves

tesa® 4319 is a heavily creped and supple paper masking tape with outstanding adhesive strength – even on rough surfaces. The masking tape has a large expansion reserve and is capable of masking even extreme corners. The masking tape resists temperatures of up to 60 °C, is simple to handle, easy to tear by hand and a valuable aid for challenging paint jobs of all kinds.

Main Application

- Masking during lacquering and painting work
- For under body repair and extreme curves
- Rapid, reliable masking off, even on rough surfaces
- Sealing and bundling

Technical Data

▪ Backing material	highly-creped paper	▪ Adhesion to steel	4.5 N/cm
▪ Total thickness	375 µm	▪ Elongation at break	58 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	28 N/cm

Properties

▪ Hand tearability	● ● ● ●	▪ Paint anchorage	● ● ● ●
▪ Suitable for rough surfaces	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

Additional Information

Recommendation:

Stretching the crêped backing guarantees evenly defined paint edges and a good adhesion.

For latest information on this product please visit <http://l.tesa.com/?ip=04319>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.