

## tesa® Professional 4688

### Standard polyethylene coated cloth tape

tesa® 4688 is a standard cloth tape with a PE-extruded substrate and a natural-rubber adhesive mass. This combination forms the basis for easy handling: the tape is easy to unroll and simple to tear by hand. The repair tape is strong but also sufficiently flexible to be a reliable aid to craftsmen. It can be used for a variety of applications and offers very good adhesion even on rough surfaces. The waterproof and ageing-resistant duct tape is available in seven colours: black, white, blue, yellow, red, silver/matt and green.

### Main Application

- Indoor and outdoor applications
- Bonding of construction films
- Bundling of cables
- Repairing, packaging, protection, marking

### Technical Data

▪ Backing material	PE extruded cloth	▪ Elongation at break	9 %
▪ Total thickness	260 µm	▪ Tensile strength	52 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance (30 min)	110 °C
▪ Adhesion to steel	3.4 N/cm	▪ Mesh	55 count per square inch

### Properties

▪ Hand tearability	● ● ●	▪ Abrasion resistance	● ● ●
▪ Straight tear edges	● ● ●	▪ Water resistance	● ● ●
▪ Certified according to	TLV 9027/01/06 for use in nuclear power plant		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04688>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.