

tesaflex® 4169 PV3 Floor Marking Tape Premium

tesa® 4169 PV3 marking tape is UV resistant and due to the thick backing it is able to withstand high mechanical stress. It is perfectly suitable for permanent marking applications.

Main Application

- Marking of working areas e. g. in factories and warehouses.
- Guiding lines for mark sensitive vehicles e. g. transport robots.
- Marking of parking spaces and gangways in offices, hospitals, at fairs etc..

Technical Data

▪ Backing material	soft PVC	▪ Adhesion to steel	1.8 N/cm
▪ Total thickness	180 µm	▪ Elongation at break	200 %
▪ Type of adhesive	acrylic	▪ Tensile strength	30 N/cm

Properties

- Suitable for sensitive surfaces ●●●
- Suitable for rough surfaces ●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

The uni colours of tesaflex® 4169 PV3 are in accordance to the RAL colour scheme.

For latest information on this product please visit <http://l.tesa.com/?ip=04169>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.